



The PulsFOG thermal fogger is perfect for the rapid application of chemicals to barns, processing plants and other livestock buildings. Designed to expel chemicals at great distances and speed, the PulsFOG reduces application time and ensures even coverage of all surfaces with a highly dense, visible fog. Perfect for the application of insecticides, vaccinations, and disinfectants.

All PulsFOGs for livestock use are sold with a heat shield or other protective device due to the flammability of certain chemistries.

PULSFOG MODEL	WEIGHT EMPTY	OUTPUT TIME	DISTANCE CHEM PROPELLED	CHEM. TANK CAPACITY	FUEL TANK CAPACITY
K-10/O	18 lbs	10L/45 Min	VK-1 100 ft	10 liter tank	2 liters
	24 Horsepower		VK-2 45 ft	2.6 gal tank	0.5 gal
Portable, 1 Nozzle					

K-10/O



PULSFOG MODEL	WEIGHT EMPTY	OUTPUT TIME	DISTANCE CHEM PROPELLED	CHEM. TANK CAPACITY	FUEL TANK CAPACITY
K-22/O	33 lbs	10L/30 Min	VK-1 160 ft	10 liter tank	2 liters
	50 Horsepower		VK-2 65 ft	2.6 gal tank	0.5 gal
Portable, 2 Nozzles					

K-22/O



PULSFOG MODEL	WEIGHT EMPTY	OUTPUT TIME	DISTANCE CHEM PROPELLED	CHEM. TANK CAPACITY	FUEL TANK CAPACITY
K-30/O	42 lbs	10L/15Min	VK-1 200 ft	10 liter tank	2 liters
	101 Horsepower		VK-2 100 ft	2.6 gal tank	0.5 gal
Portable, 2 Nozzles					

K-30/O



PULSFOG MODEL	WEIGHT EMPTY	OUTPUT TIME	DISTANCE CHEM PROPELLED	CHEM. TANK CAPACITY	FUEL TANK CAPACITY
K-30/20/O	58 lbs	30L/45Min	VK-1 200 ft	30 liter tank	20 liters
	101 Horsepower		VK-2 100 ft	7.8 gal tank	5.2 gal
Non-Portable, 2 Nozzles					

K-30/20/O



**PulsFOG BIO UNITS**– For use with heat sensitive chemical and biological agents. A second injection system consisting of an additional tank and set of nozzles uses plain water to cool the exhaust allowing many heat sensitive products to be fogged without damage. Additionally, the use of a second tank allows for larger areas to be treated without refilling. Please consult the manufacturer or Dramm for approved chemicals.

PULSFOG MODEL	WEIGHT EMPTY	OUTPUT TIME	DISTANCE CHEM PROPELLED	CHEM. TANK CAPACITY	FUEL TANK CAPACITY
K-30/20BIO	67 lbs	60L/45Min	VK-1 200 ft	2- 30 liter tanks	2- 20 liters
	101 Horsepower		VK-2 100 ft	2- 7.8 gal tanks	2- 5.2 gal
Non-Portable, 4 Nozzles					

K-30/20 BIO

