

Safety Data Sheet

FILE NAME: Safety Data Sheet
PRODUCT: Ni-CD Battery
DOCUMENT No.: M/001
EDITION: A0
DATE: 2015-10-28

EDITION	AMENDMENT	DATE OF ISSUE
A0	New Release	2015/10/28

GreenRon Energy Limited

力朗能源有限公司

Unit 11, 5/F., Tower A, New Mandarin Plaza
 14 Science Museum Road, Tsimshatsui, Kowloon, Hong Kong
 Tel : (0852) 2723 3280 Fax: (0852) 2366 0863

Notice: If the document wasn't signed and stamped, the information (subject to change without prior notice) contained in this document is for reference only and should not be used as a criterion for product guarantee or warranty.

Section 1 – Chemical Product and Company Identification

Product Name: Ni-CD Battery (Sealed rechargeable Cells)
Battery Type: Series (According to the model size and design)
Manufacturer: GreenRon Energy Limited
Address: Unit 11, 5/F., Tower A, New Mandarin Plaza
 14 Science Museum Road, TsimShaTsui, Kowloon, Hong Kong.
Tel: 0852-2723 3280
Emergency Telephone: 0852-2723 3280
Fax: 0852-2366 0863

Section 2 – Hazards Identification

Classification of the substance or mixture

Classification according to OSHA Hazard Communication Standard (29 CFR 1910.1200)



GHS08

GHS08 Health hazard

Carc. 1B H350 May cause cancer.

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of OSHA Hazard communication Standard (29 CFR 1910.1200).

· Classification system:

The classification is according to the latest edition of OSHA Hazard Communication Standard (29 CFR 1910.1200), and literature data.

Trade name: GreenRon

· Label elements

· Labelling according to OSHA Hazard Communication Standard (29 CFR 1910.1200)

· Hazard pictograms



GHS08

· Signal word Danger

· Hazard statements

H350 May cause cancer.

· Precautionary statements

Safety Data Sheet

P280 Wear protective gloves / eye protection / face protection.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 · Hazards not otherwise classified (HNOC) No further relevant information available.

Section 3 – Composition/Information on Ingredient

Chemical characterization: Mixtures

Chemical Composition	Chemical Formula	CAS No.	Weight (%)
Nickel	Ni(Carc. 2 ,H351 ;Skin Sens. 1,H317)	7440-02-0	3~5
Nickel Hydroxide	Ni(OH) ₂ (Carc. 2,H351 ; Acute Tox. 4 *,H332 ; Acute Tox. 4 * ,H302 ;Skin Sens. 1 ,H317 ;Aquatic Acute 1,H400 ;Aquatic Chronic 1 ,H410 .	12054-48-7	15~25
Cadmium	Cd (Carc. 1B ;H350)	7440-43-9	8~13
Iron	Fe	7439-89-6	25~55
Cobalt	Co(Resp. Sens. 1,H334 ;Skin Sens. 1 ,H317 ; ;Aquatic Chronic 4 ,H413)	7440-48-4	2~6
Potassium Hydroxide (Liquid)	KOH(Acute Tox. 4 *,H302 ;Skin Corr. 1A , H314)	1310-58-3	2.5~6
PP Paper	---	---	1~5
Cadmium Oxide	CdO(Muta. 2,H341 ; Repr. 2,H361fd; Acute Tox. 2 *, H330; STOT RE 1,H372 ** ; Aquatic Acute 1,H400; Aquatic Chronic 1 ,H410)	1306-19-0	8~18
Water	H ₂ O	231-791-2	4~9

Section 4 – First Aid Measures

Eyes

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

Inhalation

Safety Data Sheet

Remove from exposure and move to fresh air immediately. Use oxygen if available.

Ingestion

Do not induce vomiting. Call a physician immediately.

Section 5 – Fire Fighting Measures

Flash Point: N/A.

Auto-Ignition Temperature: N/A.

Extinguishing Media

CO₂, dry chemical.

Special Fire-Fighting Procedures

Self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Cell may vent when subjected to excessive heat-exposing battery contents

Hazardous Combustion Products

Carbon monoxide, carbon dioxide, other metallic oxide fumes. In case of PVC sleeved products, the combustion releases chloride gas.

Section 6 – Accidental Release Measures

Steps to be Taken in case Material is Released or Spilled

If the battery is accidental broken and leaks out, wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the batteries to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled material with absorbent.

Waste Disposal Method

It is recommended to discharge the battery to the end, recycle zinc, copper and other metal, handing in the abandoned batteries to related department unified, and dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental protection agency and/or federal EPA.

Section 7 – Handling and Storage

The batteries should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

Safety Data Sheet

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

Other Precautions

Do not short or install with incorrect polarity.

Section 8 – Exposure Controls, Personal Protection

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting batteries. Respiratory Protection is not necessary under conditions of normal use.

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

Personal Protection is recommended for venting batteries: Respiratory Protection, Protective Gloves, Protective Clothing and Safety Glass with side shields.

Section 9 – Physical and Chemical Properties

Nominal Voltage: 1.2V

Rated Capacity: In accordance with the specification or the product marking.

Appearance Characters: Cylindrical, with odorless battery.

Chemical Uses: Chemical power.

Section 10 – Stability and Reactivity

Stability

Stable.

Conditions to Avoid

Heating, fire, mechanical abuse and electrical abuse.

Hazardous Decomposition Products

When exposed to fire or extreme heat, batteries may emit toxic fumes.

Safety Data Sheet

Section 11 – Toxicological Information

Inhalation, skin contact and eye contact are possible when the battery is opened.

Exposure to internal contents, the corrosive fumes will be irritation to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibroid lung injury and membrane irritation.

Section 12 – Ecological Information

Environment Effect

When promptly used or disposed the battery does not present environmental hazard. In case of product destruction or opening, the metals content in a Ni-CD battery, and specifically the cadmium, are toxics for environment.

If not recycled, it must be disposed of in accordance with all state and local regulations.

Section 13 – Disposal Considerations

Incineration

Never incinerate Ni-CD batteries.

Landfill

Never dispose Ni-CD batteries as landfill.

Recycling

Ni-CD batteries can be fully recyclable. They are submitted to the European community directive 91-157/CE. We recommend proper recycling of these batteries whenever possible.

Appropriate Method of Disposal of Substance or Preparation

Dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental agency.

Section 14 – Transport Information

Sealed Ni-CD batteries with sleeve are considered as “dry batteries” which transport is not checked. They are not submitted to specific transport obligations for land, maritime (IMDG) or air (IATA) transport, as they are protected against short-circuits.

Sealed Ni-CD batteries without sleeve are submitted to ADR prescription under UNO code 2800, except in case of qualified packaging use (IATA group 2 type).

Separate batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport.

Seal Ni-CD batteries are compliant to Special Provision A123 which states: “An electrical battery or battery powered device having the potential of dangerous evolutions of heat that is not prepared so as to prevent a short-circuit.”

Safety Data Sheet

According to IATA Dangerous Goods Regulations (DGR) 56th Editions, Seal Ni-CD batteries are not subject to IATA DGR.

Section 15 – Regulatory Information

Law Information

- 《Dangerous Goods Regulation》
- 《Recommendations on the Transport of Dangerous Goods Model Regulations》
- 《International Maritime Dangerous Goods》
- 《Technical Instructions for the Safe Transport of Dangerous Goods》
- 《Classification and code of dangerous goods》
- 《Occupational Safety and Health Act》 (OSHA)
- 《Toxic Substances Control Act》 (TSCA)
- 《Consumer Product Safety Act》 (CPSA)
- 《Federal Environmental Pollution Control Act》 (FEPCA)
- 《The Oil Pollution Act》 (OPA)
- 《Superfund Amendments and Reauthorization Act Title 111 (302/311/312/313)》 (SARA)
- 《Resource Conservation and Recovery Act》 (RCRA)
- 《Safety Drinking Water Act》 (CWA)
- 《California Proposition 65》
- 《Code of Federal Regulations》 (CFR)

In accordance with all Federal, State and Local laws.

Section 16 – Additional Information

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.